



- ✓ Fast curing for minimum disruption
- ✓ Easy to apply
- ✓ Self-priming and tolerant to application on cold, damp surfaces
- ✓ Easy to clean and sterilise anti-slip surface, minimal joints
- ✓ Wide range of colour and size aggregates available
- ✓ Low maintenance can be further enhance with Page Rapid Set Seal Coat
- ✓ Life expectancy of 10 years in most environments
- ✓ Fit for traffic after approx 2 hours
- ✓ Easily passes TRL scuffing test for type 1 surfacing
- ✓ Erosion index zero (0 best, 30 worst, pass mark)
- ✓ Can achieve high slip resistance
- ✓ Texture index 1.4 (pass mark >= 1.2)

Pageset Resin Bonded Surfacing can be applied to most substrates and dependant on the type of aggregates cast onto the surface provides superior hardwearing grip and traction for both foot and vehicle traffic, maximising slip resistance and enhancing the appearance.

It is suitable for public areas, industrial, commercial, retail and domestic use such as landscaping, factories, car parks, ramps, museums, steps, platforms, footbridges, driveways, patios, roads, cycle paths, indoor markets, roof gardens and general public areas.

It assists in meeting requirements of Disability Discrimination Act 1995.

It must be laid onto a sound stable and solid base such as concrete or tarmac and can be applied to bituminous, cementitious, metal and timber. Suitable for internal & external application.

